


REACH 22

推荐安装尺寸:

Recommended Dimensions:



轴: h8 Shaft: h8

尺寸 Dimensions						传递的轴向力 Transmitted Axial Force	传递扭矩 Transmitted Torque	接触面压强 Contacting Pressure	GB70-85 12.9级锁紧螺钉 GB70-85-12.9 Locking Screw		
d	D	L	L1	L2	L3			轴 Shaft	数量 n	规格 Size	锁紧扭矩 Locking Torque
mm	mm	mm	mm	mm	mm	Ft	Mt	P			Ts
						KN	Nm	N/mm ²		Nm	
15	45	56	50	16	44	21	158	188	4	M6X45	17
16	50	56	50	16	44	21	168	176	4	M6X45	17
17	50	56	50	16	44	21	179	166	4	M6X45	17
18	50	56	50	16	44	21	190	157	4	M6X45	17
19	50	56	50	16	44	21	200	149	4	M6X45	17
20	50	56	50	16	44	21	211	141	4	M6X45	17
24	55	66	60	18.5	54	32	378	144	6	M6X55	17
25	55	66	60	18.5	54	32	394	138	6	M6X55	17
28	60	66	60	18.5	54	32	442	123	6	M6X55	17
30	60	66	60	18.5	54	32	473	115	6	M6X55	17
32	63	66	60	18.5	54	32	505	108	6	M6X55	17
35	75	83	75	22	67	39	682	98	4	M8X70	42
38	75	83	75	22	67	39	741	90	4	M8X70	42
40	75	83	75	22	67	39	780	86	4	M8X70	42
42	78	83	75	22	67	39	819	82	4	M8X70	42
45	85	93	85	24.5	76	59	1317	101	6	M8X80	42
48	90	93	85	24.5	76	59	1405	95	6	M8X80	42
50	90	93	85	24.5	76	59	1463	91	6	M8X80	42
55	94	93	85	24.5	76	78	2147	110	8	M8X80	42
60	100	93	85	24.5	76	78	2343	101	8	M8X80	42
65	105	93	85	24.5	76	78	2538	93	8	M8X80	42
70	115	110	100	29	90	93	3239	87	6	M10X95	83
75	120	110	100	29	90	93	3471	81	6	M10X95	83